



## Refuse Collection Vehicle ..... Proven Reliability



The body is made of corrosion resistance steel, reinforced with external stiffeners. Special features like gutters , sludge tanks under the body and hopper are designed specially for Asian users to suit the kind of wet waste the asians generate.



The back of the body has a raised wall to prevent spillage of overflowed exudate water onto the road whenever the truck applies brakes.



The hydraulic cylinders & hoses on the side of the tailgate are protected by a fibreglass cover , which also enhances the overall easthetic when closed .



Tailgate is raised by 2 single acting cylinders incorporated with a hose-burst valve & safety pre-set lowering speed (Tailgate stops lowering if this speed is exceeded). Additional support bar is provided for maintenance.



A durable neoprene rubber seal and the gutter on the tailgate completely eliminate any chance of leakage of slurry water onto the road during operation.



2 slurry-water tanks are provided :  
1 X ~200 ltr tank located under the tailgate & 1 X ~150 ltr tank located under the body.  
Both are equipped with 3" ball valve for quick discharge of slurry water . An additional 3" inlet is provided for internal flushing of the compartments.



Over 1 sq ft of sturdy anti-slip checker-plate platform , option for either rigid or retractable is available (above picture shows a retractable version) . Suitably positioned grab-rail is provided .